

24CP

C Models enable better leverage when handling tall timber with extended tower and faster accumulation. They feature stronger, more durable cast arms contoured for maximum support when accumulating as well as an ultra-reliable disc drive with easily adjustable bearings.



24CP

STANDARD CONFIGURATION

METRIC

IMPERIAL

| WEIGHTS & DIMS. | Fixed Rotation | 2,926 kg | 6,450 lbs |
|-----------------|--------------------------------|---------------------|---------------------|
| | Height | 2,972 mm | 117" |
| | Width | 1,778 mm | 70" |
| | Depth | 1,854 mm | 73" |
| | Maximum Throat Opening | 1,321 mm | 52" |
| | Maximum Throat Opening @ Teeth | 1,092 mm | 43" |
| | Accumulation Area | 0.54 m ² | 5.8 ft ² |

| DISC | Cutting Capacity | 610 mm | 24" |
|------|--|-----------|---------|
| | Tip-to-Tip Diameter | 1,549 mm | 61" |
| | Rated Saw Speed | 1,075 rpm | |
| | Number of Teeth | 18 | |
| | Saw Kerf | 59 mm | 2 5/16" |
| | Weight (<i> Holders & Teeth Varies Depending on Disc </i>) | 434 kg | 956 lbs |
| | Style (<i> One Piece or Segmented </i>) | Both | |

| SAW DRIVE | Motor | Rexroth | |
|-----------|------------|---------|--|
| | Motor Size | 170 cc | |